

Model: Power-Xtra PX18650-20B - 3.7V 2000 Mah Li-ion Battery- 3C

Stock Code: 900.600.503.320

TECHNICAL INFORMATIONS		
Item	Specifications	Conditions
Nominal Voltage	3.7±0.05V	0.2C Discharge
Charging	Method	CC-CV
	Voltage	4.20±0.05V
Typ. Capacity	2.000 mAh	0.2C discharge
Standard Charge Current	1.000 mAh (0.5C)	Constant current at 1000mA charge to 4.20V, then constant
		voltage at 4.20V charge till current decline to ≤20mA
Standard Discharging Current	400 mAh (0.2C)	400mA to 2.75V
Max. Discharge Current	2.000 mAh (1.0C)	1.0C / 2000 mAh to 2.75V
Maximum Continuous	6.000 mAh (3.0C)	3.0C
Discharge Current		3.00
Temperature	Charge	0 to +45°C
	Discharge	-20 to +60°C
	Storage	Less than 1 year: -20~25°C
		less than 3 months: -20~40°C
Weight	43 gr	approximately
Cycles Test	During this cycle life test, the ambient temperature should be kept at 23°C ±2°C. The cell	
	shall be charged at CC/CV=0.5C/4.20V, cut off till current decline to 0.05C, stored for 10mins,	
	then discharged at a constant current of 0.5C to a final voltage of 2.75V, after that, stored	
	10mins prior to next charge/ discharge cycle.	
	The cell shall be continuously charged and discharged for 300 times .	

IMAGE

Technical Drawing		Image
Diameter	18.7 mm	
Height	65.5 mm	ttery
		PCWER-XTRA PX18650-208 37V 2000 mA

REV002 Revised Date:24.11.2020