



## 7.0 İnc Nextion HMI Display Kapasitif Ekran

### Nextion Models

Nextion Type	Intelligent Series
Nextion Models	NX8048P070-011C (Capacitive touchscreen without enclosure)

### Specifications

	Data	Description
Color	64K 65536 colors	16 bit 565, 5R-6G-5B
Layout size	181mm(L)×108mm(W)×9.3mm(H)	NX8048P070-011C
Active Area (A.A.)	164.90mm(L)×100.00mm(W)	
Visual Area (V.A.)	154.08mm(L)×85.92mm(W)	
Resolution	800×480 pixel	Also can be set as 480×800
Touch type	Capacitive	
Touches	> 1 million	
Backlight	LED	
Backlight lifetime (Average)	>30,000 Hours	

Brightness	300nit	0% to 100%, the interval of adjustment is 1%
Weight	310g	

### Electronic Characteristics

	Test Conditions	Min	Typical	Max	Unit
Operating Voltage		4.75	5	6.5	V
Operating Current	VCC=+5V, Brightness is 100%	–	430	–	mA
	SLEEP Mode	–	170	–	mA
Power supply recommend : <b>5V, 1.0A, DC</b>					

### Working Environment & Reliability Parameter

	Test Conditions	Min	Typical	Max	Unit
Working Temperature	5V, Humidity 60%	-20	25	70	°C
Storage Temperature		-30	25	85	°C
Working Humidity	25°C	10%	60%	90%	RH

### Interfaces Performance

	Test Conditions	Min	Typical	Max	Unit
Serial Port Baudrate	Standard	2400	9600	921600	bps
Output High Voltage (TXD)	IOH=1mA	3.0	3.2		V
Output Low Voltage(TXD)	IOL=-1mA		0.1	0.2	V

Input High Voltage(RXD)		2.0	3.3	5.0	V
Input Low Voltage(RXD)		-0.7	0.0	1.3	V
Serial Port Mode	3.3V/5.0V TTL				
Serial Port	4Pin_2.54mm				
USB interface	NO				
SD card socket	Yes (FAT32 format), support maximum 32G Micro SD Card * microSD card socket is exclusively used to upgrade Nextion firmware /HMI design				
Extended IO	8 Digital extended GPIO				
	IO0-IO7 support input, output and component binding event				
	IO6-IO7 support PWM				
RTC	built-in RTC support (Battery type: CR1220)				

## Memory Features

Memory Type	Test Conditions	Min	Typical	Max	Unit
FLASH Memory	Store fonts and images			120	MB
User Storage	EEPROM			1024	BYTE
RAM Memory	Store variables			512	KB
Instruction Buffer	Instruction Buffer			1024	BYTE

## Audio Features

Speaker	Parameter	Min	Typical	Max	Unit
Power	16Ω 0.5W		0.5		W

Size	Φ40*5.2H				mm
------	----------	--	--	--	----

**\* NX8048P070-011C do not have speaker in the package.**

### **Product Dimensions**

NX8048P070-011C\_Dimension