



SPECIFICATION FOR APPROVAL

CUSTOMER:		DATE:
PART NO: RC0608U-1R0M		DWG.NO: RB3613009
CUSTOMER PART NO:		CUST.DWG.NO:
(1) DIMENSION(UNIT: mm) 		A 9.5 (MAX) m/m
		B 11.0 (MAX) m/m
		C 10.0 (MIN) m/m
		D 3.0 (REF) m/m
		E 0.65 ± 0.1 m/m
		F m/m
		G m/m
		H m/m
		(2)ELECTRICAL REQUIREMENTS
L (uH)	1 ± 20%	
RDC (mΩ)	15 (MAX)	
IDC (A)	2 (MAX)	
TEST CONDITION	1KHz / 0.25V	
(4)MATERIAL LIST		
NO/ITEM	MATERIAL	SUPPLIER
CORE	K3B DR2W 6×8 F3-4-3 或同等級	FEIJIN
WIRE TYPE	2UEW φ 0.4×1C 或同等級	TAIPINGYANG
WINDING	5.5TS (REF)	
TUBE	UL φ 6×10mm 或同等級	GODDESS
		APPROVED BY 吳載敏
		CHECKED BY 張明德
		DRAWN BY Summer

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw

TEST DATA

CUSTOMER:				DATE:				
PART NO: RC0608U-1R0M				DWG.NO: RB3613009				
CUSTOMER PART NO :				CUST.DWG.NO :				
TEST CONDITION: 1KHz / 0.25V				DIMENSION (UNIT : mm)				
ITEM	L (uH)	RDC (mΩ)	IDC (A)	A	B	C	D	E
SPEC	1 ±20%	15 (MAX)	2 (MAX)	9.5 (MAX)	11.0 (MAX)	10.0 (MIN)	3.0 (REF)	0.65 ± 0.1
1	1.0	10	OK	7.5	9.5	15.0	3.0	0.63
2								
3								
4								
5								
6								
7								
8								
9								
10								
\bar{X}								
R								
TEST INSTRUMENTS CH101 CH301A						APPROVED BY 吳載敏		
						CHECKED BY 張明德		
						DRAWN BY Summer		

CORE MASTER ENTERPRISE CO., LTD.

TEL:886-2-8919-1288 FAX:886-2-8919-1298 WEB:www.coremaster.com.tw